

Product Data Sheet		SLn									
Model	SLn150 SLn200 SLn254 SLn300 SLn345 SLn430 SLn500 SLn600 SLn660										
Type	Double Side - Single Side										
Cleaning Rollers	Designed and Manufactured in the UK										
Construction	Designed in the UK										
Machine Covers	Brushed Stainless Steel										
Machine parts	Aluminium - Stainless Steel - Delrin										
Motors	N/A										
Controls " Host Line " Line Running Signal	24v DC										
Software	N/A										
Anti Static System	SIMCO Netherlands										
Anti Static Bar	1 x MEB or 2 x MEB Simco										
Pneumatics	SMC										
Power Supply Unit	N/A										
Bearings	SKF Japan										
Effective Cleaning width	150mm	200mm	254mm	300mm	345mm	430mm	500mm	600mm	660mm		
Services	Electrical Machine	24v DC / 110vAC / 230vAC									
	Static Transformer	110 / 240v AC 50/60Hz									
	Power consumption - Machine	0.4 Watts / 0.97 Watts / 1.6 Watts									
	Power consumption - Static	55 Watts									
	Air Pressure	5 - 7 bar									
	Air Pipe	4mm OD									
	Air Quality	Oil Free/Dry									
	Air Consumption	0.10048L/Cycle									
Cleaning Rollers x 1 or x 2	Base Material	Nanocleen - Urethane - 55Å Film - Silicone - 35Å Panel - Silicone - 25Å Ultracleen - Silicone - 60Å UTF - Silicone - 25Å									
	MAREP	Mini Adhesive Roll Eco Paper									
	MAREF	Mini Adhesive Roll Eco Film									
	Overall Standard	ISO 6123 Class A - Part 1 - 2 - 3									
	Straightness	0.1mm/m									
	Roller Diameter	Ø 37.4mm									
	Construction	Aluminium Tube & Stainless Steel Spigots									
	Adhesive Rolls x 1 or x 2	Base Material	ECO -Moisture Stable Paper - Temp - Max 120°C / Min 5°C ECO - Polypropylene - Temp - Max 120°C / Min 5°C Water Based Acrylic Adhesive ECO - Packaging Throughout								
Diameters - Ø		ID - 38mm / OD - 52mm & 57mm									
Max / Min Temp		Max 70°C / Min 5°C									
Machine Weight - DS Unit Data		3Kg	3.6Kg	4.6KG	5.4Kg	6.2Kg	7.7Kg	9Kg	10.8KG	11.9Kg	
Load Per Standing Foot		N/A									
Pass Height	N/A										
Operation	Mode	N/A									
	Flow direction	L - R or R - L									
	Speed Range	0.1 - 150m/min									
	Speed Accuracy	Web Driven									
Mounting Options	Standard Mounting Brackets										
Diverter Roller Options " DS Unit "	Not Available										
Diverter Roller Options " SS Unit "	Not Available										